



**ALUMINIJSKI
PROZORI I VRATA**



**ALUMINUM
WINDOWS AND DOORS**



ALUMINIJUM - ALUMINIUM TE 50

FRAME WIDTH ŠIRINA OKVIRA	50 mm
SASH WIDTH ŠIRINA KRILA	58 mm
SYSTEM WALL THICKNESS DEBLJINA	1.40 mm
NUMBER OF CHAMBERS BROJ KOMORA	5
GLASS THICKNESS DEBLJINA STAKLA	4 – 32 mm
ACCESSORY SELECTION IZBOR DODATAKA	Profiles with Euronorm channels Profiles suitable for PVC accessory (Multi Point Lock). Profili sa Euronorm kanalima Profili pogodni za PVC pribor (Multi Point Lock)
OPENING TYPES NAČINI OTVARANJA	Single-sash window, double-sash window, transom window, inward-opening single sash door, inward-opening double-sash door, outward-opening single-sash door, outward-opening double-sash door. Jednokrilni prozor, dvokrilni prozor, jednokrilna vrata koja se otvaraju prema unutra, dvokrilna vrata koja se otvaraju prema unutra, jednokrilna vrata koja se otvaraju prema van, dvokrilna vrata koja se otvaraju prema van.



ALUMINIJUM - ALUMINIUM TE 62

FRAME WIDTH ŠIRINA OKVIRA	62 mm
SASH WIDTH ŠIRINA KRILA	65 mm
SYSTEM WALL THICKNESS DEBLJINA	1.30 mm
INSULATION BARRIER IZOLACIJSKA BARIJERA	24 mm
NUMBER OF CHAMBERS BROJ KOMORA	5
GLASS THICKNESS DEBLJINA STAKLA	10 – 45 mm
ACCESSORY SELECTION IZBOR DODATAKA	Profiles with Euronorm channels Profiles suitable for PVC accessory (Multi Point Lock). Profili sa Euronorm kanalima Profili pogodni za PVC pribor (Multi Point Lock).
OPENING TYPES NAČINI OTVARANJA	Single-sash window, double-sash window, transom window, inward-opening single sash door, inward-opening double- sash door, outward-opening single-sash door, outward- opening double-sash door, folding door, parallel sliding. Jednokrilni prozor, dvokrilni prozor, jednokrilna vrata koja se otvaraju prema unutra, dvokrilna vrata koja se otvaraju prema unutra, jednokrilna vrata koja se otvaraju prema van, dvokrilna vrata koja se otvaraju prema van, preklopna vrata, paralelno-klizna vrata.



ALUMINIJUM - ALUMINIUM TE 85

FRAME WIDTH ŠIRINA OKVIRA	77 mm
SASH WIDTH ŠIRINA KRILA	85 mm
FOLDING MEASURE MJERA PREKLAPANJA	8 mm
POLYAMIDE TAPES POLIAMIDNE TRAKE	34 mm
FILLING DEPTH DUBINA PUNJENJA	30-64 mm
ACCESSORY SELECTION IZBOR DODATAKA	Profiles with Euronorm channels Profiles suitable for PVC accessory (Multi Point Lock). Profili sa Euronorm kanalima Profili pogodni za PVC pribor (Multi Point Lock).
DESCRIPTION OPIS	Thermo 85 is a profile with an interrupted thermal bridge. This means that the heat does not escape from the building through the metal surfaces of the profile, but the interruption of heat transfer by the insulating material is achieved. Termo 85 je profil sa toplotnim mostom. To znači da toplina ne izlazi iz zgrade kroz metalne površine profila, već se postiže prekid prijenosa topline izolacijskim materijalom.